



May 20, 2022

Albert Lankford  
1 ClosetMaid Drive  
Grantsville, MD 21536  
(301) 895-4566

Dear Albert,

We are pleased to offer the following proposal for your consideration:

**CRESSWOOD EF-48-75SR LOW RPM GRINDER**

<u>Type of Material:</u>	<u>Screen Size:</u>	<u>Output Goal: (lbs./hr.)</u>
Particle Board	¾"	3,200 to 4,200

• **Machine Specifications**

Floor Area of unit: 80" X 166"  
Frame Thickness: ¾"  
Net weight: 6,000 lbs

• **Cutterhead Geometry**

Two row premium cupped 1 ¼" inserts (Qty: 56)  
Grinding head diameter: 10"  
Grinding head length: 48"

• **Drive Package**

75 HP  
480V/60Hz/3Ph  
Grinding Head Speed: 400-600 RPM  
Double Row Spherical Roller Bearings

• **Infeed**

Input Capacity: 5" x 48"  
Load sensitive feed roll

• **Discharge**

Air

• **Feed Roll**

Positive grip with replaceable grippers (Qty: 154)  
Air assisted counter weighted for various heights of material  
Able to grind both blocks and edgings at the same time

• **Control Package**

UL Listed  
Load sensor  
Hour meter  
Digital cutterhead amp meter

• **Screen Size**

1 screen set in your choice of perforation size  
Sizes available: ⅜", ½", ⅝", ¾", 1", 1 ¼", 1 ½"

Cresswood EF-48-75 SR Low RPM Grinder  
Includes: Control Panel

~~12,200.00~~

**Options:**

~~Webster Chain Conveyor~~

~~10,400.00~~

~~MODEL FSM FLAT SPRING VIBRATING CONVEYOR 18/24W X 6D X 3/16 THK. PAN X 15'-3" LG. WITH P5000 DRIVE 2 HP 1200 RPM MOTOR, ADJ. MOTOR BASE, V-BELT DRIVE AND GUARD~~

Webster Chain Conveyor

~~12,200.00~~

MODEL FSL FLAT SPRING VIBRATING CONVEYOR 42/48W X 4D X 3/16 THK. PAN X 23'-8" LG. WITH P3000 DRIVE 3 HP 1200 RPM MOTOR, ADJ. MOTOR BASE, V-BELT DRIVE AND GUARD

SPECIAL FEATURES INCLUDE: EXTRA WIDE PAN W/ DOUBLE WIDE BASE FOOT PRINT DRIVE AND MOTOR AT FEED END HOG INFEED INTO EF48 CRESSWOOD GRINDER INFEED TO HAVE 16" LG. WELD-IN COVER

shaker pan

1 - 8Hr. Day of Start Up and Training

~~3,000.00~~

**Total:**

~~27,600.00~~